

Metal Slitter Shear / up to 1,6 mm

Common features:

- cutting without distortion or straightening of formed parts
- burr free cutting
- no finishing of the edges is required
- accurate cutting along a marked line
- single-side trimming is possible
- working speed up to 5 m/min
- cutting of U-,C- and L-profiles
- open view to scribed line or template
- long life tool
- easy, one hand, operation
- simple and safe to use
- noise under limit regulations
- an insulated and suppressed motor
- can cause no injury while in motion

Advantages 1016-1:

- fast, cheap and universal shear for installers, assembly, crafts, and drywall profiles
- the light, compact and robust shear is used in the assembly as well as in mass production
- linear guide systems can be used to mount the slitter

For UA-profile (2 mm) use type 3515.

1016-1



Also available:

→ cordless, type AK 3016 (12 or 18 Volt)




Metal box 18000



Optional adjustable guide S/01, for precisely straight cut strips without marking a line 100, 250 and 500 mm





max. cutting ca	Art.nr.:	01010-1	
steel	400 N/mm ²	mm/ga.	1,6 / 16
stainless steel	600 N/mm ²	mm/ga.	1,3 / 18
stainless steel	800 N/mm ²	mm/ga.	1,0 / 19
aluminium	250 N/mm ²	mm/ga.	2,5 / 12
tightest radius		mm	140
working speed	Ŀ	m/min	7
strokes		min ⁻¹	3900
motor capacity		Watt	300
weight		kg	1,6



1016-1				
spare parts				
knife standard	0101	3	knife serrated	01013z
set of jaws	BG1307	' 4		•
knife-pin set	BG1255	55		-
optional access	ories			
metal-box	-		-	18000
adjustable guide	S/01	up	to 100 mm	10059
adjustable guide	S/01	up	to 250 mm	10060
adjustable guide	S/01	up	to 500 mm	10061
support roller (me	etal)		-	BG10077

BG=Set other voltages available all units are ready to use