

3514-7R

Radius Seam Metal Shear / up to 2,0 mm Ideal for small radius through multiple seams and/or heavy duty

Good curve ability


Cold and emission-free operation

Common features:

- cuts without distortion or straightening of formed parts
- burr free cutting
- no finishing of the edges is required
- accurate cutting along a marked line
- single-side trimming is possible.
- clear view to scribed line or template
- long life tool
- easy, one hand, operation
- simple and safe to use
- noise under limit regulations
- insulated and suppressed motor
- almost no maintenance necessary
- knife and jaws can be reground
- parts are standardized and interchangeable
- no flying sparks!
- no dangerous handling with angle grinders!
- Interior suitable
- accident free!

Ideal for:

- cutting slots in ducting and metals of all kinds
- Air and climate technology installers
- TRUCK workshops
- metalworking companies etc.



spiral ducting

starting hole 12-14 mm Ø accurate cutting along a marked line

Also available:

- → cordless, type AK 3514-7R
- → pneumatic, type19/3514-7R

DRÄCO Radius Seam Metal Shear		type	3514-7R
max. cutting capacity		Art.no.	61080
steel	400 N/mm ²	mm/ga.	2,0 / 14
stainless steel	600 N/mm ²	mm/ga.	1,5 / 16
stainless steel	800 N/mm ²	mm/ga.	1,3 / 18
aluminium / non ferro	250 N/mm ²	mm/ga.	3,0 / 10
duct- & Pittsburgh Seam	400 N/mm ²	mm/ga.	4 x 0,75 / 21
tightest radius		mm/ "	45 / 1¾
working speed ±		m/min	5-7
strokes		min -1	2400
motor capacity		Watts	500
weight		kg	2
starting hole	_	Ø mm	14

3514-7R	
spare parts	
knife heavy duty	371401
set of jaws	BG37222
knife-pin set	BG35055

optional accessories		
metal-box	18000	
knife serrated heavy duty	371401Z	



all units are ready to use BG=Set other voltages available